

BEKA RUBBER


Flooring that meets your needs

Technical Data Sheet: BeHobby
Revision: Feb 2023

BeHobby

BeHobby rubber tiles are a very versatile product. These tiles provide high impact absorption and ensures protection against a possible fall, which makes them the perfect solution for playgrounds, wall climbing facilities, terraces, walking paths, balconies, etc.

Manufactured specifically for outdoor use, BeHobby tiles have flat bottom surface and are intended for installation on hard surfaces (concrete, cement, etc).



COMPOSITION

Recycled SBR Rubber, MDI polyurethane bonding agent, color pigments.

SPECIFICATIONS

Usage	Outdoor
Size	500 x 500mm ($\pm 1,5\%$)
Thickness	20 mm / 25mm / 30mm / 40mm / 50mm ($\pm 2\%$)
Color	■ ■ ■
Surface	Porous, soft
Density	900-930 kgs/m ³
Weight/m ²	18 kg (20 mm) / 23 kg (25 mm) / 26,5 kg (30 mm) / 34 kg (40 mm) / 42 kg (50 mm)
Hardness	55 \pm 3 Shore A

Beka Spor Zeminleri San. Ve Dış Tic. Ltd. Şti.
Factory : Saray Mh. 222 Cd. NO: 16/A, 06980
KAHRAMANKAZAN / ANKARA - TURKEY
+90 850 480 2352 – info@bekasport.com



BEKA RUBBER

Flooring that meets your needs

Technical Data Sheet: BeHobby
Revision: Feb 2023

APPLICATION AREAS




Depending on the thickness selected playgrounds, wall climbing facilities, terraces, walking paths, balconies, garage paths, etc.

CHOOSE YOUR THICKNESS

BeHobby 20 mm	50 cm HIC
BeHobby 25 mm	60 cm HIC
BeHobby 30 mm	70 cm HIC
BeHobby 40 mm	100 cm HIC
BeHobby 50 mm	130 cm HIC

CERTIFICATIONS

Fire Resistance	Efl (B2)a,c (EN 13501)
Reaction to Fire	Fs <150 mm in 20 seconds (ISO 11925)
Permitted Fall Height	Complies with EN 1177:2018
HIC 1000	Complies with EN 1176-1:2017
Regulation (EC) n. 1907/2006 (REACH), Annex XVII, Point 62 (Mercury compounds)	Complies
Regulation (EC) n. 1907/2006 (REACH), Annex XVII, Point 23.1 (Cadmium and its compounds)	Complies
Regulation (EC) n. 1907/2006 (REACH), Annex XVII, Point 20 (Organostannic compounds)	Complies
Abrasion resistance	0,74 gr. (ISO 5470-1)

-  **Superb impact absorption**
-  **Quick and easy installation**
-  **Easy cleaning and maintenance**

This TDS is for information purposes only and Beka Sport may change the specifications of this TDS without prior notice. Beka Sport will not be responsible for any misuse of this TDS. The latest version of this TDS can be found on the website www.bekarubber.com.

Beka Spor Zeminleri San. Ve Dış Tic. Ltd. Şti.
Factory : Saray Mh. 222 Cd. NO: 16/A, 06980
KAHRAMANKAZAN / ANKARA - TURKEY
+90 850 480 2352 – info@bekasport.com

